

# Einsatzempfehlung

## Einsatzempfehlung für MH- PowerBlade Sägebänder Auswahl des Sägebandes zum sägen von Vollmaterial:

Variable Zahnteilung ZpZ (Zähne pro Zoll)	Schnittlänge in mm	
	von	bis
10-14		30
8-12	20	50
6-10	25	60
5-8	35	80
4-6	50	100
3-4	80	150
2-3	120	350
1,4-2	250	600

## Auswahl des Sägebandes zum sägen von Rohren und Profilen:

WS in mm	Rohr Ø in mm / Zahnteilung Tz in ZpZ									
	20	40	60	80	100	120	150	200	300	400
2	14	14	14	14	14	14	10-14	10-14	8-12	8-12
3	14	14	10-14	10-14	10-14	10-14	8-12	8-12	6-10	6-10
4	14	14	10-14	10-14	8-12	8-12	8-12	8-12	5-8	5-8
5	14	10-14	10-14	10-14	8-12	8-12	8-12	6-10	5-8	5-8
6	14	10-14	10-14	8-12	8-12	8-12	8-12	5-8	5-8	4-6
8	14	10-14	8-12	8-12	8-12	6-10	6-10	5-8	4-6	4-6
10		8-12	6-10	6-10	6-10	5-8	5-8	4-6	4-6	4-6
12		8-12	6-10	6-10	5-8	5-8	4-6	4-6	4-6	3-4
15		8-12	6-10	5-8	5-8	4-6	4-6	4-6	3-4	3-4
20			6-10	5-8	4-6	4-6	4-6	3-4	3-4	3-4
30				4-6	4-6	4-6	3-4	3-4	3-4	2-3
50						3-4	3-4	3-4	2-3	2-3
75								2-3	2-3	2-3
100									2-3	2-3
150										2-3

\* WS= Wandsstärke

Weitere Sägebänderausführungen(z.B. Hartmetall) auf Anfrage lieferbar.  
 Stand Dezember 2010